













ULTRA TRIEUR GTEA



Ultra Trieur is an important machine which is used for separating seeds, barley, broken or long grains and strange particles from the wheat. A cylinder pressed pocket rounds to separate the seed over the plate. Seed fall to the canal at the middle of the cylinder, and then spiral carrier at the middle of the canal throw the seeds away.

Iron plate cylinders which has different pockets used for long grains, for example, ball-shaped grains and barleys. Same chassis, long and circular type of trieur can be made in respect of requirement. Special machines has control system, which are capable to decompose wheat and wheat shaped seed. While starting movement or stopping of the cylinder, it has not load over because of using a special reducer according to requirement of the customer, speed control device can be used for controlling of the motor at desired ratio. This process makes optimum separation.

TYPE		DIMENSIONS (mm)					CAPACITY t/h	AIR NEEDED		MOTOR			Approx Weight Kg.		
GTEA		A	B	C	D	E		m³	mmWS	CEI Standard	Kw	rpm	Net	Gross	Package m³
Seed	72/3000/2	1370	2180	3470	3860	1060	9-11	16	18	2xAGM 132 S6	3	940	1930	2050	11.6
Seed	72/3000/3	1370	2950	3470	3860	1060	13-16	18	20	3xAGM 132 S6	3	940	2890	3010	15.6



- 1 - Wheat
- 2 - Broken Wheat
- 3 - Small Wheat
- 4 - Barley
- 5 - Long Thin Grain
- 6 - Seed

